

ZK507-W

4K UHD high brightness laser projector



- **Bright 4K UHD laser projector - 5000 ANSI lumens**
- **HDR Compatible**
- **1.6 x zoom, vertical lens shift**
- **30,000 hours maintenance-free laser light source**

tbd



Specifications

EAN: 5055387663619, Colour: White

UPC: 796435 44 445 7, Colour: White

Display/image	
Display technology	DLP™
Resolution	UHD (3840x2160)
Brightness	5,000 lumens
Contrast ratio	300,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9
Displayable colours (millions)	1073.4
Horizontal scan rate	31 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	70%
Screen size	0.67m ~ 7.68m (26.45" ~ 302.2") diagonal
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	1.39:1 ~ 2.22:1
Projection distance (m)	1.3m - 9.3m
Zoom	1.6
Zoom type	Manual
Focal length (mm)	20.91mm~32.62mm/0.823"~1.284"
Lens shift	Vertical +15%, Horizontal: +/-0%
Native offset	100%
Lens shift	Yes - [downloads_link]
Connectivity	
Connections	Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power 1.5A Control 1 x USB-A service, 1 x RS232, 1 x RJ45, 1 x 12V trigger
General	
Noise level (min)	30dB
Noise level (max)	32dB
PC compatibility	UHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	UHD: 2160p(24/50/60Hz) / HDTV: 720p(50/60Hz), 1080i(50/60Hz), 1080p(24/50/60Hz) / SDTV : 480i/p, 576i/p
3D compatibility	Frame packing, Side-by-Side, Top-and-Bottom
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	9 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
24/7 operation	Yes
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Remote control	Backlit ProAV remote
Speaker count	2
Watts per speaker	5W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit
Networking	
LAN - control	Yes
Power	
Power supply	100V ~ 240V, 50-60Hz
Power consumption (standby)	<0.5W
Power consumption (min)	274W
Power consumption (max)	423W
Weight and dimensions	
Dimensions (W x D x H) mm	498 x 331 x 171
Gross weight	12.4 kg
Net weight	10.54 kg

