


HD29H Big screen gaming, sports and movies





- Lights on viewing 3400 lumens
- 4K UHD and HDR compatible
- Lightning fast gaming projector Supports 1080p 120Hz with 8.4ms response time
- Easy connectivity 2x HDMI, MHL, USB Power and 10W speaker

Convenient and easy to setup, the bright and versatile HD29H boasts HDR compatibility as well as delivering high contrast and accurate true to life colour reproduction. This compact projector is ideal for HDR gaming with support for 1080p 120Hz which provides a lightning fast response time of 8.4ms. You can even use it for watching live sport , TV shows and movies.



Specifications

Dianlov/imaga	
Display/image Display technology	DLP
Resolution	1080p Full HD (1920x1080)
Brightness	3.400 lumens
Contrast ratio	50.000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85(120 for 3D)Hz
Uniformity	80%
Screen size	0.71m ~ 7.65m (28" ~ 301") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	203 6000 (Bright) 15000 (Duppmin) 10000 (Eq.)
Lamp life hours (up to)	6000 (Bright), 15000 (Dynamic), 10000 (Eco)
Optical Throw ratio	1.47:1 ~ 1.62:1
Projection distance (m)	1.47:1 ~ 1.62:1 1m - 9.8m
Zoom	1.1
Zoom type	Manual
Focal length (mm)	15.59 ~ 17.14
Native offset	116%
Connectivity	
Connections	Inputs 1 x HDMI 2.0, 1 x HDMI
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	Control 1 x 3D sync
General	
Noise level (typical)	25dB
Noise level (max)	27dB
PC compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 4K UHD (24/30/50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Backlit home remote
Speaker count	1
Watts per speaker	10W
In the box	AC power cord, remote control, Battery, basic user manual
Input lag	8.40ms
Optional wireless models Power	WHD200
Power Power supply	100 ~ 240V, 50 ~ 60Hz
Power supply Power consumption	0.5W
(standby)	0.077
Power consumption (min)	205W
Power consumption (max)	295W
Weight and dimensions	
Net weight	2.87kg
	316 x 244 x 108
Dimensions (W x D x H)	010 / 211 / 100





Copyright © 2018, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 1206202025137