

EH515TST

Powerful short throw solution



© Samruh Creative Association

- **Ultra bright Full HD 1080p projector – 5000 ANSI lumens**
- **Short throw lens - 100" image from less than two metres away**
- **Vertical and horizontal lens shift**
- **Four corner geometric projection**

Designed for demanding professional installations, the high-specification EH515TST full HD short throw projector boasts a brightness of 5000 lumens and is connection ready with HDBaseT, two HDMI inputs, MHL compatibility, DisplayPort and multiple analogue and audio connections. Equipped with four corner geometric correction and an impressive lens shift, the flexibility of the EH515TST ensures the image is exactly where it is meant to be, even on uneven walls and when projector placement is awkward.



Specifications

Display/image	
Display technology	DLP
Resolution	1080p Full HD (1920x1080)
Brightness	5,000 lumens
ANSI brightness	5,000 lumens
Contrast ratio	10,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Has vertical auto keystone correction	Yes
Displayable colours (millions)	1073.4
Horizontal scan rate	15.375 ~ 91.146Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	80%
Screen size	0.73m ~ 76.2m (28.59" ~ 3000") (diagonal)
Lamp info	
Light source type	Lamp
Lamp watts	365
Lamp life (hours)	3000 (Bright), 5000 (Eco+)
Optical	
Throw ratio	0.79:1
Projection distance (m)	0.5m - 5.3m
Zoom type	Fixed
Focal length (mm)	11.66
Lens shift	Vertical +25%, Horizontal +10%
Native offset	105%
Connectivity	
Connections	<p>Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support, 1 x DisplayPort, 2 x VGA (YPbPr/RGB), 1 x Composite video, 1 x S-Video, 1 x HDBaseT, 1 x Audio RCA L&R, 2 x Audio 3.5mm, 1 x Mic 3.5mm</p> <p>Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x 12V trigger, 1 x Wired remote, 1 x Audio 3.5mm</p> <p>Control 1 x RS232, 1 x mini USB mouse/service</p>
General	
Noise level (typical)	28dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar,Kensington Lock,Password protected interface
OSD / display languages	25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,German,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian, (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese
24/7 operation	Yes
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Backlit ProAV remote
Speaker count	2
Watts per speaker	10W
In the box	AC power cord Remote control, 2x AAA batteries Basic user manual
Networking	
LAN - control	Yes
Power	
Power supply	100V ~ 240V ± 10%, 50-60Hz
Power consumption (standby)	0.5W
Power consumption (min)	340W
Power consumption (max)	425W
Weight and dimensions	
Net weight	5.2kg
Dimensions (W x D x H) mm	424 x 344 x 160

