

## EH335

High resolution, versatile and powerful









- Bright 1080p projector 3600 ANSI lumens
- Easy connectivity 2x HDMI, MHL, USB Power, RJ45
- Clear, powerful audio 10W speaker
- Lightweight and portable

Beam bright, eye catching content with the Full HD 1080p EH335 projector. Perfect for classroom and meeting room presentations, this projector is designed to be used at any time of day.

Additionally, it boasts easy connectivity with multiple inputs including two HDMI, MHL, VGA and a built in 10W speaker. You can even use the USB Power to connect and power HDMI dongles such as the Google Chromecast.



## **Specifications**

EAN: 5055387660137, Colour: White

Display/image Display technology

DIPTM

Resolution 1080p Full HD (1920x1080)

Brightness 3,600 lumens Contrast ratio 20.000:1 Native aspect ratio 16:9 Aspect ratio - compatible 4:3 +/-40° Keystone correction - vertical

15.38 ~ 91.15Khz Horizontal scan rate 50 ~ 85(120 for 3D)Hz Vertical scan rate

Uniformity 70%

Screen size 0.71m ~ 7.65m (28" ~ 301") diagonal

Lamp info Light source type Lamp 240 Lamp watts

Lamp life hours (up to) 4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)

Optical Throw ratio

1.47:1 ~ 1.62:1 Projection distance (m) 1m - 9.8m Zoom 1.1 Zoom type Manual Focal length (mm) 15.59 ~ 17.14 Native offset 116%

Connectivity Connections

Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x

Audio 3.5mm

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232, 1 x RJ45

General

Noise level (typical) 27dB 29dB Noise level (max)

PC compatibility WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA,

Mac

2D compatibility

NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 3D compatibility 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

3D

Security bar, Kensington Lock, Password protected interface Security OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

 $5^{\circ}\text{C} \sim 40^{\circ}\text{C}$ , Max. Humidity 85%, Max. Altitude 3000m Operating conditions

Remote control Card style Speaker count Watts per speaker

In the box AC power cord, remote control, Battery, basic user manual Optional wireless models HDCast Pro, QuickCast Bundle, QuickCast starter kit,

WHD200

Networking LAN - control

Yes Power

Power supply 100 ~ 240V, 50 ~ 60Hz Power consumption (standby) 0.5W

Power consumption (min) 205W 295W Power consumption (max)

Weight and dimensions

Dimensions (W x D x H) mm 316 x 244 x 108 Gross weight 3.88 kg 3.29 kg Net weight



