

W512

Bright and versatile



- **Bright WXGA projector – 5500 ANSI lumens**
- **Installation flexibility – Vertical lens shift and 1.6x zoom**
- **Ultimate Control - Crestron, Extron, AMX, PJ-Link and Telnet LAN commands**
- **Horizontal keystone and four corner adjustment**



Designed for professional installation environments, meeting rooms and classrooms, the powerful high-specification W512 projector boasts high brightness for lights on projection.

For more complex installations, this projector is equipped with a large zoom range, vertical lens shift, HV keystone and four corner adjustment - ideal for uneven walls or awkward installations with difficult angles.

Specifications

Display/image	
Display technology	DLP™
Resolution	WXGA (1280x800)
Brightness	5,500 lumens
Contrast ratio	15,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - horizontal	+/-20°
Keystone correction - vertical	+/-20°
Has vertical auto keystone correction	Yes
Horizontal scan rate	15,375 ~ 91.146Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	85%
Screen size	0.65m ~ 7.65m (25.66" ~ 301.15") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	330
Lamp life hours (up to)	3000 (Bright), 6000 (Dynamic), 5000 (Eco), 7000 (Eco+)
Optical	
Throw ratio	1.48:1 ~ 2.35:1
Projection distance (m)	1.3m - 9.6m
Zoom	1.6
Zoom type	Manual
Focal length (mm)	20.91 ~ 32.62
Lens shift	Vertical +16%
Native offset	96%
Connectivity	
Connections	<p>Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm, 1 x USB-A reader/wireless</p> <p>Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x 12V trigger</p> <p>Control 1 x RS232, 1 x RJ45, 1 x 3D sync</p>
General	
Noise level (typical)	30dB
Noise level (max)	32dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Remote control	Data remote with laser and mouse function
Speaker count	2
Watts per speaker	10W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	QuickCast Bundle, QuickCast starter kit, WHD200, WUSB
Networking	
LAN - control	Yes
LAN - display	Yes
LAN - wireless networking	Yes - optional
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	310W
Power consumption (max)	390W
Weight and dimensions	
Dimensions (W x D x H) mm	369 x 295 x 132
Gross weight	6.02 kg
Net weight	5.12 kg

